

SCOPE :

This specification applies to the Pb Free high current type SMD inductors for
MSCDB-2206H-SERIES


PRODUCT IDENTIFICATION

MSCDB - 2206H - 4R7 M

① ② ③ ④

- ① Product Code
- ② Dimensions Code
- ③ Inductance Code
- ④ Tolerance Code

(1) SHAPES AND DIMENSIONS



A: 22.3Max.	mm
B: 16.2Max.	mm
C: 7.40Max.	mm
D: 14.5Typ.	mm

(2) ELECTRICAL SPECIFICATIONS

SEE TABLE 1

TEST INSTRUMENTS

- L : HP 4284A PRECISION LCR METER (or equivalent)
- RDC : CHROMA MODEL 16502 MILLIOHMMETER (or equivalent)

(3) CHARACTERISTICS

- (3)-1 Ambient temperature +60°C Max.
- (3)-2 Operate temperature range -40°C ~ +125°C
(Including self temp. rise)
- (3)-3 Storage temperature range -40°C ~ +125°C



TABLE 1

MAGLAYERS PT/NO.	Inductance L(μH)	Percent Tolerance	Test Frequency	Resistance RDC(Ω)Max.	Rated DC Current		Marking
					IDC1(A)	IDC2(A)	
MSCDB-2206H-R80□	0.8	M,N	100kHz/0.25V	2.76m	35.0	16.0	R80
MSCDB-2206H-1R2□	1.2	M,N	100kHz/0.25V	4.20m	30.0	15.0	1R2
MSCDB-2206H-1R8□	1.8	M,N	100kHz/0.25V	5.40m	25.0	13.0	1R8
MSCDB-2206H-2R7□	2.7	M,N	100kHz/0.25V	8.40m	20.0	10.0	2R7
MSCDB-2206H-3R3□	3.3	M,N	100kHz/0.25V	9.36m	17.0	9.0	3R3
MSCDB-2206H-4R7□	4.7	M,N	100kHz/0.25V	10.6m	15.0	8.5	4R7
MSCDB-2206H-5R6□	5.6	M,N	100kHz/0.25V	14.9m	14.0	7.8	5R6
MSCDB-2206H-6R8□	6.8	M,N	100kHz/0.25V	17.0m	12.0	7.5	6R8
MSCDB-2206H-8R2□	8.2	M,N	100kHz/0.25V	18.6m	11.0	7.0	8R2
MSCDB-2206H-100□	10	M,N	100kHz/0.25V	20.6m	10.0	6.5	100
MSCDB-2206H-120□	12	L,M	100kHz/0.25V	28.3m	9.5	5.5	120
MSCDB-2206H-150□	15	L,M	100kHz/0.25V	33.6m	9.0	5.0	150
MSCDB-2206H-180□	18	L,M	100kHz/0.25V	39.6m	8.0	4.6	180
MSCDB-2206H-220□	22	L,M	100kHz/0.25V	47.3m	6.5	4.0	220
MSCDB-2206H-270□	27	L,M	100kHz/0.25V	52.2m	6.0	3.8	270
MSCDB-2206H-330□	33	L,M	100kHz/0.25V	70.1m	5.5	3.4	330
MSCDB-2206H-390□	39	K,M	100kHz/0.25V	78.0m	5.2	3.2	390
MSCDB-2206H-470□	47	K,M	100kHz/0.25V	0.109	5.0	2.8	470
MSCDB-2206H-560□	56	K,M	100kHz/0.25V	0.116	4.5	2.6	560
MSCDB-2206H-680□	68	K,M	100kHz/0.25V	0.134	4.0	2.4	680
MSCDB-2206H-820□	82	K,M	100kHz/0.25V	0.173	3.5	2.2	820
MSCDB-2206H-101□	100	K,M	100kHz/0.25V	0.202	3.0	2.0	101
MSCDB-2206H-121□	120	K,M	100kHz/0.25V	0.230	3.0	1.6	121
MSCDB-2206H-151□	150	K,M	100kHz/0.25V	0.250	2.6	1.5	151
MSCDB-2206H-181□	180	K,M	100kHz/0.25V	0.300	2.5	1.3	181
MSCDB-2206H-221□	220	K,M	100kHz/0.25V	0.380	2.4	1.2	221
MSCDB-2206H-271□	270	K,M	100kHz/0.25V	0.470	2.2	1.1	271
MSCDB-2206H-331□	330	K,M	100kHz/0.25V	0.560	1.9	1.0	331
MSCDB-2206H-391□	390	K,M	100kHz/0.25V	0.680	1.7	0.9	391
MSCDB-2206H-471□	470	K,M	100kHz/0.25V	0.850	1.4	0.82	471
MSCDB-2206H-561□	560	K,M	100kHz/0.25V	1.00	1.3	0.78	561
MSCDB-2206H-681□	680	K,M	100kHz/0.25V	1.10	1.2	0.72	681
MSCDB-2206H-821□	820	K,M	100kHz/0.25V	1.40	1.1	0.64	821
MSCDB-2206H-102□	1000	K,M	100kHz/0.25V	1.80	1.0	0.56	102


※ □ specify the inductance tolerance, K(±10%), L(±15%), M(±20%), N(±30%)

※ IDC1 : Based on inductance change ($\Delta L/L_0 : \leq$ drop 10% Typ.)@ ambient temp. 25°C

IDC2 : Based on temperature rise ($\Delta T : 40^\circ\text{C}$ Typ.)

Rated DC Current : The less value which is IDC1 or IDC2.

(4) RELIABILITY TEST METHOD MECHANICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Substrate bending	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage or electrical damage.	<p>The sample shall be soldered onto the printed circuit board in figure 1 and a load applied until the figure in the arrow direction is made approximately 3mm.(keep time 30 seconds) PCB dimension shall the page 7/9</p> <p style="text-align: center;">F(Pressurization)</p>  <p style="text-align: center;">PRESSURE ROD figure-1</p>
Vibration	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	<p>The sample shall be soldered onto the printed circuit board and when a vibration having an amplitude of 1.52mm and a frequency of from 10 to 55Hz/1 minute repeated should be applied to the 3 directions (X,Y,Z) for 2 hours each. (A total of 6 hours)</p>
Solderability	New solder More than 90%	<p>Flux (rosin, isopropyl alcohol{JIS-K-1522}) shall be coated over the whole of the sample before hard, the sample shall then be preheated for about 2 minutes in a temperature of 130~150°C and after it has been immersed to a depth 0.5mm below for 3±0.2 seconds fully in molten solder M705 with a temperature of 245±5°C.</p> <p>More than 90% of the electrode sections shall be covered with new solder smoothly when the sample is taken out of the solder bath.</p>



MECHANICAL

TEST ITEM	SPECIFICATION	
Resistance to Soldering heat (reflow soldering)	There shall be no damage or problems.	<p style="text-align: center;">Temperature profile of reflow soldering</p> <p>The specimen shall be passed through the reflow oven with the condition shown in the above profile for 1 time.</p> <p>The specimen shall be stored at standard atmospheric conditions for 1 hour, after which the measurement shall be made.</p>

ELECTRICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Dielectric withstand voltage	There shall be no other damage or problems.	AC 100V voltage shall be applied for 1 minute across the top surface and the terminal of this sample
Temperature characteristics	$\Delta L/L20^{\circ}\text{C} \leq \pm 10\%$ $0 \sim 2000 \text{ ppm}/^{\circ}\text{C}$	The test shall be performed after the sample has stabilized in an ambient temperature of -20 to $+85^{\circ}\text{C}$, and the value calculated based on the value applicable in a normal temperature and normal humidity shall be $\Delta L/L20^{\circ}\text{C} \leq \pm 10\%$.




ENVIROMENT CHARACTERISTICS

TEST ITEM	SPECIFICATION																
High temperature storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in an atmosphere with a temperature of $85 \pm 2^\circ\text{C}$ and a normal humidity. Upon completion of the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Low temperature storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in an atmosphere with a temperature of $-25 \pm 3^\circ\text{C}$. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Change of temperature	$\Delta L/Lo \leq \pm 5\%$ There shall be no other damage of problems	The sample shall be subject to 5 continuous cycles, such as shown in the table 2 below and then it shall be subjected to standard atmospheric conditions for 1 hour, after which measurement shall be made. <div style="text-align: center;"> table 2 <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th style="text-align: center;">Temperature</th> <th style="text-align: center;">Duration</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)</td> <td style="text-align: center;">30 min.</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">Standard atmospheric</td> <td style="text-align: center;">No.1→No.2</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">$85 \pm 2^\circ\text{C}$ (Thermostat No.2)</td> <td style="text-align: center;">30 min.</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">Standard atmospheric</td> <td style="text-align: center;">No.2→No.1</td> </tr> </tbody> </table> </div>		Temperature	Duration	1	$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)	30 min.	2	Standard atmospheric	No.1→No.2	3	$85 \pm 2^\circ\text{C}$ (Thermostat No.2)	30 min.	4	Standard atmospheric	No.2→No.1
	Temperature	Duration															
1	$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)	30 min.															
2	Standard atmospheric	No.1→No.2															
3	$85 \pm 2^\circ\text{C}$ (Thermostat No.2)	30 min.															
4	Standard atmospheric	No.2→No.1															
Moisture storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in a temperature of $40 \pm 2^\circ\text{C}$ and a humidity(RH) of 90~95%. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity more than 1 hour.															
Test conditions : The sample shall be reflow soldered onto the printed circuit board in every test.																	




(6) PACKAGING


(6)-1 CARRIER TAPE DIMENSIONS (mm)



(6)-2 TAPING DIMENSIONS (mm)



(6)-3 REEL DIMENSIONS (mm)



(6)-4 QUANTITY

300pcs/Reel

The products are packaged so that no damage will be sustained.



MAG.LAYERS