



Networking Communication Components

RT Series

LAN Transformer


Part number: RT11H10

Part name :10/ 100 Transformer Single Port


Feature

- Compliant and peak reflow temperature rating 245°C .
- Meets IEEE802.3 specification.
- Excellent common mode noise suppression.
- Packaging specification is tube.
(RT11H□□ : Tube)




Part number code




Mechanical Dimension and Marking



UNIT	mm	inch
A	11.75 +0.254/-0.254	0.463 +0.010/-0.010
B	6.90 +0.254/-0.254	0.272 +0.010/-0.010
C	4.50 +0.254/-0.254	0.177 +0.010/-0.010
D	3.20 +0.254/-0.254	0.126 +0.010/-0.010
E	0.50 +0.127/-0.127	0.020 +0.005/-0.005
F	2.00 +0.127/-0.127	0.079 +0.005/-0.005
G	10.00 +0.254/-0.254	0.394 +0.010/-0.010
H	5.00 +0.254/-0.254	0.197 +0.010/-0.010
I	0.50 +0.254/-0.254	0.020 +0.010/-0.010



Suggested Land Pattern




UNIT	mm	inch
a	10.00	0.394
b	5.00	0.197
c	2.00	0.079
d	$\varnothing 0.90$	$\varnothing 0.035$

Drawn	Yuxuan.Xiang	Designed	Yuxuan.Xiang	Approved	James.Cheng
-------	--------------	----------	--------------	----------	-------------

Schematics

RT11H10




Electrical Specification @ 25°C, Humidity 65% RH

Inductance @ Phy side(OCL)
100KHz, 0.1V, 8mA DC Bias
350uH MIN

Part Number	Turn Ratio		Insertion Loss	Return Loss				CMRR	Crosstalk	Hipot
	100KHz		dB MAX	dB MIN				dB MIN	dB MIN	Vrms, Sec
	TX	RX		0.5-30 MHz	40 MHz	60 MHz	80 MHz			
RT11H10	1:1±5%	1:1±5%	-1.1dB	-18dB	-15dB	-13dB	-11dB	-20dB	-35dB	Pri To Sec @60Hz,1mA 1500, 60

Operating Temperature: 0°C to +70°C.
Storage Temperature: -25°C to +105°C
JSDEC Moisture: Level 1.

Wave Soldering



- Tip Temperature :265°C MAX.
- Tip Temperature Time: 4sec MAX.