



# Networking Communication Components

## RT Series

### **LAN Transformer**


Part number: RT22H06

Part name :Giga Transformer Two Port

### **Feature**


- Compliant and peak reflow temperature rating 245°C .
- Meets IEEE802.3 specification.
- Excellent common mode noise suppression.
- Packaging specification is tube.  
( RT22H□□ : Tube )

### **Part number code**






REV.	Description	Date	Drawn	Designed	Approved
A	Specification issued	04.01.2013	Yuxuan.Xuang	Yuxuan.Xiang	James.Cheng


# Mechanical Dimension and Marking



UNIT	mm	inch
A	28.10 +0.25/-0.25	1.107 +0.010/-0.010
B	11.10 +0.25/-0.25	0.437 +0.010/-0.010
C	11.00 +0.25/-0.25	0.433 +0.010/-0.010
D	3.00 +0.25/-0.25	0.118 +0.010/-0.010
E	0.30 +0.05/-0.05	0.012 +0.002/-0.002
F	1.00 +0.05/-0.05	0.039 +0.002/-0.002
G	2.00 +0.05/-0.05	0.079 +0.002/-0.002
H	23.00 +0.25/-0.25	0.906 +0.010/-0.010
I	Ø0.40	Ø0.016
J	5.33 +0.25/-0.25	0.210 +0.010/-0.010
K	8.89 +0.25/-0.25	0.350 +0.010/-0.010



# Suggested PWB Layout




UNIT	mm	inch
a	28.10	1.107
b	23.00	0.906
c	11.10	0.437
d	8.89	0.350
e	5.33	0.210
f	2.00	0.079
g	1.78	0.070
h	1.00	0.039

Drawn	Yuxuan.Xiang	Designed	Yuxuan.Xiang	Approved	James.Cheng
-------	--------------	----------	--------------	----------	-------------

# Schematics

RT22H06




## Electrical Specification @ 25°C, Humidity 65% RH

Inductance @ Phy side(OCL)  
 100KHz, 0.1V, 8mA DC Bias  
 350uH MIN

Part Number	Turns Ratio	Insertion Loss	Return Loss					DMCR			Crosstalk			Hipot
	100KHz	dB MAX	dB MIN					dB MIN			dB MIN			Vrms, Sec
	± 5%	1MHz-100MHz	1MHz-30MHz	40MHz-50MHz	60MHz-80MHz	100MHz	30MHz	60MHz	100MHz	30MHz	60MHz	100MHz	Pri To Sec	
RT22H06	1:1	-1.0	-18	-14.4	-13.1	-12	-10	-43	-37	-33	-40	-35	-30	1500, 60


Operating Temperature: 0°C to +70°C.  
 Storage Temperature: -25°C to +105°C  
 JSDEC Moisture: Level 1.

## Wave Soldering





- Tip Temperature :265°C MAX.
- Tip Temperature Time: 4sec MAX.


## Package Specification





TUBE MECHANICAL DIMENSION  
Units : mm Tolerances : x.xx  $\pm 0.3$   
0.xx  $\pm 0.1$



INNER CARTON : 545 x 120 x 115



2 BOX / CARTON



EXPORT CARTON : 545 x 255 x 125

1. TUBE = 18 PCS
2. INNER CARTON = 48 TUBE =  $48 \times 18$  PCS = 864 PCS
3. EXPORT CARTON = 2 INNER CARTON =  $2 \times 864$  PCS = 1728 PCS